

Rotary Tillers

RTA12 Series

Features	Benefits
American made	American made means better parts availability. Many tillers are imported.
Tractor HP range 42" & 50" 58" & 60" 74"	15-35 HP 20-40 HP 25-50 HP
3 Year Gearbox Warranty	3 Years on housings, seals, bearings. Shows our confidence in the product.
42", 50", 58", 66" & 74" Working widths	A wide range of widths are available to meet specific customer needs.
6 1/2" Digging depth	For deep soil penetration.
Formed plate steel upper hitch	Plate steel is stronger than flat bar type hitch.
Clevis lower hitch	Provides additional strength and easy one person hook-up.
Offset Capabilities	Allows tiller to work closer to objects such as fence lines, buildings and trees.
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up. Does not offset to the left with Quick-Hitch.
Adjustable Parking stand	Allows for easy hook-up and storage.
Adjustable skid shoes	Control depth with various settings.
Formed and reinforced rear deflector	Forming gives deflector additional strength. Adjustable deflector allows for various finish results.
4 'C' Shaped heat-treated tines per flange	'C' Shaped tines require less HP to move through the ground.
Solid steel rotor shaft	Solid steel shaft gives rotor extra strength.
15" Rotor swing diameter	For deep tilling and turning the soil over faster.
Double lip seal on rotor bearing	Double lip seal helps keep the dirt out and the grease in.
Fully shielded slip-clutch driveline	Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.
#80 Drive chain enclosed in oil bath	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.
Stamped chain case cover	Stamped forming gives the chain cover strength.

Rotary Tillers

RTR12 Series

Features	Benefits
American made	American made means better parts availability. Many tillers are imported.
Tractor HP range 42" & 50" 58" & 60" 74"	15-35 HP 20-40 HP 25-50 HP
Reverse tilling action	Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
3 year Gearbox Warranty	3 Years on housing, seals, & bearings. shows our confidence in the product.
42", 50", 58", 66" & 74" Working widths	A wide range of widths are available to meet specific customer needs.
6 1/2" Digging depth	For deep soil penetration.
Bent plate steel upper hitch	Plate steel is stronger than flat bar type hitch.
Clevis lower hitch	Provides additional strength and easy one person hook-up.
Offset Capabilities	Allows tiller to work closer to objects such as fence lines, buildings and trees.
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up. (Offset cannot be used with Quick-Hitch.)
Adjustable parking stand	Allows for easy hook-up and storage.
Adjustable skid shoes	Control depth with seven adjustments.
Formed and reinforced rear deflector	Keeps dirt in and leaves a level finish. Forming gives deflector additional strength. Adjustable deflector allows for various finish results.
Front deflector	Front deflector is flexible to take the beating from rocks or debris.
4 'C' shaped heat-treated tines per flange	'C' Shaped tines require less HP to move through the ground.
Solid steel rotor shaft	Solid steel shaft gives rotor extra strength.
15" Rotor swing diameter	For deep tilling and turns the soil over faster.
Double lip seal on rotor bearing	Double lip seal helps keep the dirt out and the grease in.
Fully shielded slip-clutch driveline	Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.
#80 Drive chain enclosed in oil bath	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.
Stamped chain case cover	Stamped forming gives the chain cover strength.