FM25 SERIES FLAIL MOWERS

33-80 HP | Cat. 1 & 2




Sturdy and compact.

Land Pride's FM25 Series Flail Mowers are built for use in vineyards, orchards, and recreational areas and will fit a wide variety of tractors. The spring-loaded belt-tensioning system makes it easy to tension belts for longer life. Cutting height is variable from 0" to 6". The rear access door and quick-change D-ring system (Duckfoot knives only) simplifies blade changes.






Optional brush rake teeth keep material in to pulverize it.



The dynamically balanced rotor is driven by a three section PowerBand® belt and mounted on spherical roller bearings.



Unique spring-loaded belt-tensioning system brings belt to proper tension by turning a nut. (N/A on 48")



Three different blade options make quick work of grass, grapevine shoots, saplings, and tree prunings.

	FM2560	FM2572	FM2584
Horsepower	33-80 HP	42-80 HP	49-80 HP
Hitch	Cat. 1	Cat. 1 & 2	
Weight - lb (kg)	929 (421)	1,040 (472)	1,168 (530)
Working Width (cm)	60" (152)	72" (183)	84" (213)
Overall Width	72"	84"	96"
Drive Cover Height	33"		
Rotor RPM	2,450		
Gearbox Rating	80 HP	80 HP	80 HP
Driveline	Cat. 4		
Offset Hitch	Center, 8" Right	Center, 10" Right	
Blade Tip Speed	12,046 fpm		
Knives Attachment	D-Ring for Light Blades, C-Clamp for Heavy Blades		
Duckfoot Blades (Qty)	24	28	32
Heavy Y Blades (Qty)	32	40	48
Hammer Blades (Qty)	16	20	24
Rotor Bearings	Spherical Roller Bearing		
Brush Rakes (optional)	8	9	11
Rotor Diameter	5" with Reinforcing Bars		
Rotor Rotation	Reverse		
Cutting Height	0"-6"		
Cutting Capacity	Duckfoot Knives: 1" Heavy-Duty Y Knives: 1.5" Hammer Knives: 2"		
Rear Roller Diameter	5.56"		
Hood/Deck Thickness	10 Gauge		
Color			

PowerBand® is a Registered Trademark of the Gates Corporation

QUICK HITCH SYSTEM

*See dealer for complete warranty information.